

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 1532
Print date: 02.08.2024
Version: 3.0

Dichtol
Revision date: 26.02.2024
Issue date: 26.02.2024

EN
Page 1 / 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. product identifiers

Article No. (manufacturer/supplier) 1532
Trade name/designation Dichtol
WFT
UFI: MRV0-NOQM-P00S-G3KW

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Metalimpregnation / capillary-active sealing

1.3. Details of the supplier of the safety data sheet

supplier (manufacturer/importer/downstream user/distributor)

Diamant Polymer GmbH
Marie-Bernays-Ring 3a Telephone: +49(0)2166-98360
41199 Mönchengladbach Telefax: +49(0)2166-83025

Department responsible for information:

Lab
E-mail (competent person) info@diamant-polymer.de

1.4. Emergency telephone number

Emergency telephone number +49(0)2166-98360
Only available during office hours.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.
STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Danger

Hazard statements

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P241 Use explosion-proof electrical equipment.
P261 Avoid breathing vapours.
P264 Wash hands thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves and eye/face protection.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/attention.
P310 Immediately call a POISON CENTER or doctor/ physician.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 1532
Print date: 02.08.2024
Version: 3.0

Dichtol
Revision date: 26.02.2024
Issue date: 26.02.2024

EN
Page 2 / 9

P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P370 + P378 In case of fire: Use extinguishing powder or sand to extinguish.
P501 Dispose of contents/container to industrial incineration plant.

Hazard components for labelling

2-methylpropan-1-ol
n-butyl acetate

Supplemental hazard information

not applicable

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description Mixed solvent + polymer mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. Index No.	REACH No. Designation classification // Remark	weight-%
204-658-1 123-86-4 607-025-00-1	01-2119485493-29-XXXX n-butyl acetate Flam. Liq. 3 H226 / STOT SE 3 H336 / EUH066	50 - 100
201-148-0 78-83-1 603-108-00-1	01-2119484609-23-XXXX 2-methylpropan-1-ol Flam. Liq. 3 H226 / STOT SE 3 H335 / Skin Irrit. 2 H315 / Eye Dam. 1 H318 / STOT SE 3 H336	20 - 25

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 1532
Print date: 02.08.2024
Version: 3.0

Dichtol
Revision date: 26.02.2024
Issue date: 26.02.2024

EN
Page 3 / 9

Unsuitable extinguishing media

strong water jet

5.2. **Special hazards arising from the substance or mixture**

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. **Advice for firefighters**

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. **Personal precautions, protective equipment and emergency procedures**

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. **Environmental precautions**

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. **Methods and material for containment and cleaning up**

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. **Reference to other sections**

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. **Precautions for safe handling**

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. **Conditions for safe storage, including any incompatibilities**

Requirements for storage rooms and vessels

Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 20 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. **Specific end use(s)**

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. **Control parameters**

Occupational exposure limit values:

not applicable

DNEL:

n-butyl acetate

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 1532
Print date: 02.08.2024
Version: 3.0

Dichtol
Revision date: 26.02.2024
Issue date: 26.02.2024

EN
Page 4 / 9

Index No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4
DNEL acute dermal, short-term (systemic), Workers: 11 mg/kg
DNEL long-term dermal (systemic), Workers: 11 mg/kg
DNEL acute inhalative (local), Workers: 600 mg/m³
DNEL acute inhalative (systemic), Workers: 600 mg/m³
DNEL long-term inhalative (local), Workers: 300 mg/m³
DNEL long-term inhalative (systemic), Workers: 300 mg/m³
DNEL short-term oral (acute), Consumer: 2 mg/kg
DNEL long-term oral (repeated), Consumer: 2 mg/kg
DNEL acute dermal, short-term (systemic), Consumer: 6 mg/kg
DNEL long-term dermal (systemic), Consumer: 6 mg/kg
DNEL acute inhalative (local), Consumer: 300 mg/m³
DNEL acute inhalative (systemic), Consumer: 300 mg/m³
DNEL long-term inhalative (local), Consumer: 35,7 mg/m³
DNEL long-term inhalative (systemic), Consumer: 35,7 mg/m³

2-methylpropan-1-ol

Index No. 603-108-00-1 / EC No. 201-148-0 / CAS No. 78-83-1
DNEL long-term inhalative (local), Workers: 310 mg/m³
DNEL long-term oral (repeated), Consumer: 25 mg/kg
DNEL long-term inhalative (local), Consumer: 55 mg/m³

PNEC:

n-butyl acetate

Index No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4
PNEC aquatic, freshwater: 0,18 mg/L
PNEC aquatic, marine water: 0,018 mg/L
PNEC aquatic, intermittent release: 0,36 mg/L
PNEC sediment, freshwater: 0,981 mg/kg
PNEC sediment, marine water: 0,0981 mg/kg
PNEC, soil: 0,0903 mg/kg
PNEC sewage treatment plant (STP): 35,6 mg/L

2-methylpropan-1-ol

Index No. 603-108-00-1 / EC No. 201-148-0 / CAS No. 78-83-1
PNEC aquatic, freshwater: 0,4 mg/L
PNEC aquatic, marine water: 0,04 mg/L
PNEC aquatic, intermittent release: 11 mg/L
PNEC sediment, freshwater: 1,52 mg/kg
PNEC sediment, marine water: 0,152 mg/kg
PNEC, soil: 0,0699 mg/kg
PNEC sewage treatment plant (STP): 10 mg/L

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: Nitrile rubber or butyl rubber

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 1532
Print date: 02.08.2024
Version: 3.0

Dichtol
Revision date: 26.02.2024
Issue date: 26.02.2024

EN
Page 5 / 9

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. **Information on basic physical and chemical properties** *

Physical state:	Liquid
Colour:	refer to label
Odour:	characteristic
Odour threshold:	not applicable
Melting point/freezing point:	not applicable
Initial boiling point and boiling range:	108 °C Source: 2-methylpropan-1-ol
Flammability:	Flammable liquid and vapour.
Lower and upper explosion limit:	
Lower explosion limit:	1,2 Vol-% Source: n-butyl acetate
Upper explosion limit:	11 Vol-% Source: 2-methylpropan-1-ol
Flash point:	= 25 °C Method: DIN 53213-1
Auto-ignition temperature:	390 °C Source: n-butyl acetate
Decomposition temperature:	not applicable
pH at 20 °C:	not applicable
Viscosity at 20 °C:	12 s 4 mm Method: DIN 53211
Cinematic viscosity (40°C):	20 mm²/s
Solubility(ies):	
Water solubility at 20 °C:	insoluble
Partition coefficient: n-octanol/water:	see section 12
Vapour pressure at 20 °C:	9,9014 mbar
Density and/or relative density:	
Density at 20 °C:	0,88 g/cm³
Relative vapour density:	not applicable
particle characteristics:	not applicable

9.2. **Other information** *

Solid content:	9,69 weight-%
solvent content:	
Organic solvents:	90 weight-%
Water:	0 weight-%

SECTION 10: Stability and reactivity

10.1. **Reactivity**

No information available.

10.2. **Chemical stability**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. **Possibility of hazardous reactions**

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. **Conditions to avoid**

Hazardous decomposition byproducts may form with exposure to high temperatures.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 1532
Print date: 02.08.2024
Version: 3.0

Dichtol
Revision date: 26.02.2024
Issue date: 26.02.2024

EN
Page 6 / 9

10.5. Incompatible materials

not applicable

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

n-butyl acetate

oral, LD50, Rat: 10.760 mg/kg

dermal, LD50, Rabbit: > 14.112 mg/kg

Method: OECD 402

inhalative (vapours), LC50, Rat: 23,4 mg/L (4 h)

Method: OECD 403

2-methylpropan-1-ol

oral, LD50, Rat: > 2.830 mg/kg

dermal, LD50, Rabbit: 3.400 mg/kg

inhalative (vapours), LC50, Rat: 24,6 mg/L (4 h)

Skin corrosion/irritation; Serious eye damage/eye irritation

Causes skin irritation.

Causes serious eye damage.

n-butyl acetate

Skin, OECD 404, Rabbit (4 h): Evaluation non-irritant.

eyes, OECD 405, Rabbit (4 h): Evaluation non-irritant.

2-methylpropan-1-ol

Skin, OECD 404, Rabbit (4 h)

skin corrosion/irritation

eyes, OECD 405, Rabbit (4 h)

Respiratory or skin sensitisation

n-butyl acetate

Skin, OECD 406, Guinea pig: Evaluation not sensitising.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

n-butyl acetate

Germ cell mutagenicity; Evaluation Ames test negative.

Method: Ames test

STOT-single exposure; STOT-repeated exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

n-butyl acetate

Specific target organ toxicity (single exposure), drowsiness Evaluation May cause drowsiness or dizziness.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 1532 Dichtol
Print date: 02.08.2024 Revision date: 26.02.2024
Version: 3.0 Issue date: 26.02.2024

EN
Page 7 / 9

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

12.1. Toxicity

n-butyl acetate

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 18 mg/L (96 h)

Daphnia toxicity, EC50, Daphnia magna: 44 mg/L (48 h)

Algae toxicity, ErC50, Scenedesmus subspicatus: 647,7 mg/L (72 h)

2-methylpropan-1-ol

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 1.430 mg/L (96 h)

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 1.100 mg/L (48 h)

Algae toxicity, ErC50, Pseudokirchneriella subcapitata: 1.799 mg/L (72 h)

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080111* Waste paint and varnish containing organic solvents or other dangerous substances

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number or ID number

UN 1263

14.2. UN proper shipping name

Land transport (ADR/RID):

Paint

Sea transport (IMDG):

PAINT

Air transport (ICAO-TI / IATA-DGR):

Paint

14.3. Transport hazard class(es)

3

14.4. Packing group

III

14.5. Environmental hazards

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 1532
Print date: 02.08.2024
Version: 3.0

Dichtol
Revision date: 26.02.2024
Issue date: 26.02.2024

EN
Page 8 / 9

Land transport (ADR/RID) not applicable
Marine pollutant not applicable

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

Tunnel restriction code D/E

Sea transport (IMDG)

EmS-No. F-E, S-E

14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according IBC - Code.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC-value (in g/L): 791

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

EC No. CAS No.	Designation	REACH No.
204-658-1 123-86-4	n-butyl acetate	01-2119485493-29-XXXX
201-148-0 78-83-1	2-methylpropan-1-ol	01-2119484609-23-XXXX

SECTION 16: Other information

Full text of classification in section 3

Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3	Flammable liquids	On basis of test data.
Skin Irrit. 2	Skin corrosion/irritation	Calculation method.
Eye Dam. 1	Serious eye damage/eye irritation	Calculation method.
STOT SE 3	STOT-single exposure	Calculation method.
STOT SE 3	STOT-single exposure	Calculation method.

Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 1532
Print date: 02.08.2024
Version: 3.0

Dichtol
Revision date: 26.02.2024
Issue date: 26.02.2024

EN
Page 9 / 9

DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

* Data changed compared with the previous version